



125 SERIES TFH

HIGH FLOW

Available in Stainless Steel and Brass

TECHNICAL SPECIFICATIONS

Features:	Robust Design - Great durability	
	Safety sleeve to prevent accidental disconnection.	
	Optional depressurizer (C.U.R.P.*) that evacuates residual pressure during connection.	
	Double O-ring for optimal sealing..	
Operating pressure:	Up to 450 Bar	
Materials:	Body:	Carbon Steel EN -10277-3
	O-rings:	NBR / VITON / EPDM
	Back-up-ring:	PTFE
	Springs:	EN 10270-1/SH
	Balls:	AISI 1010/1015
Available Threads:	BSP *	
Closing System:	Poppet Valve or C.U.R.P.**	
Connection:	Sleeve Retraction & Press to connect	
Disconnection:	Sleeve Retraction	
Connection Under Pressure:	Not Allowed / Only C.U.R.P. version	

Available Size: 1/4" a 1 1/2"

Working Temperature (O-rings)

NBR	Viton	EPDM
+100°C	+200°C	+150°C
-30°C	-10°C	-40°C

Sectors: Industrial



Applications: Designed for Hydraulic Oil (Group II-2014/68/EU)

Interchange: RECTUS TEMA T-SERIES
CEJN Series 525

*Others upon request.

MODEL STRUCTURE

Example:

125.12312 AC

Series	Material	Part	Closing	O-rings	Size (S)	Thread
125.	1 Carbon St.	1 Male	0 Without	0 Without	1 6	1/4"
	2 SS316	2 Female	1 Poppet	1 NBR	2 10	3/8"
	4 Brass		3 C.U.R.P	2 VITON	3 13	1/2"
				3 EPDM	4 20	3/4"
					5 25	1"
					7 40	1 1/2"

**CURP = Connection Under Pressure Residual / Not available in 1/4" size

125-1

INTEVA reserves the right to make modifications to its products without prior notice. Any external or internal alterations to our products will automatically void the warranty.







125 SERIES TFH

HIGH FLOW


(S) 6 - 1/4"




STANDARD MALE MODELS

(S)	ØA	REF.		CH1	ØD	L1	L
6	1/4" BSP	125.11111AB	450	19	12	45	81

STANDARD FEMALE MODELS

(S)	ØA	REF.		CH2	ØB	L2	L
6	1/4" BSP	125.12111AB	450	22	21	64	81

(S) 10 - 3/8"



STANDARD MALE MODELS

(S)	ØA	REF.		CH1	ØD	L1	L
10	3/8" BSP	125.11112AC	350	22	20	38	74

STANDARD FEMALE MODELS

(S)	ØA	REF.		CH2	ØB	L2	L
10	3/8" BSP	125.12112AC	350	30	34	60	74

125-2

INTEVA reserves the right to make modifications to its products without prior notice. Any external or internal alterations to our products will automatically void the warranty.






125 SERIES TFH

HIGH FLOW


(S) 13 - 1/2"




STANDARD MALE MODELS

(S)	ØA	REF.		CH1	ØD	L1	L
13	1/2" BSP	125.11113AD	300	27	24.7	42	82

STANDARD FEMALE MODELS

(S)	ØA	REF.		CH2	ØB	L2	L
13	1/2" BSP	125.12113AD	300	36	40	65	82

(S) 20 - 3/4"



STANDARD MALE MODELS

(S)	ØA	REF.		CH1	ØD	L1	L
20	3/4" BSP	125.11114AE	280	36	32.7	46	91

STANDARD FEMALE MODELS

(S)	ØA	REF.		CH2	ØB	L2	L
20	3/4" BSP	125.12114AE	280	41	52	72	91

125-3

INTEVA reserves the right to make modifications to its products without prior notice. Any external or internal alterations to our products will automatically void the warranty.






125 SERIES TFH

HIGH FLOW



(S) 25 - 1"




STANDARD MALE MODELS

(S)	ØA	REF.		CH1	ØD	L1	L
25	1" BSP	125.11115AF	250	46	40.8	63	115

STANDARD FEMALE MODELS

(S)	ØA	REF.		CH2	ØB	L2	L
25	1" BSP	125.12115AF	250	46	62	88	115

(S) 40 - 1 1/2"



STANDARD MALE MODELS

(S)	ØA	REF.		CH1	ØD	L1	L
38	1 1/2" BSP	125.11117AH	200	60	48.5	107	173

STANDARD FEMALE MODELS

(S)	ØA	REF.		CH2	ØB	L2	L
38	1 1/2" BSP	125.12117AH	200	60	73	112	173

125-4

INTEVA reserves the right to make modifications to its products without prior notice. Any external or internal alterations to our products will automatically void the warranty.



v11



125 SERIES TFH

CAPS &
PLUGS

Designed to protect female (coupler) and male (nipple) parts while they are disconnected.


MODEL STRUCTURE / DIMENSIONS

Example:

125.5373 AA

Series	Material	Part	Color	Size (S)	Type
125.	5 Plastic	3 Plug 4 Cap	7 Grey	1 6 1/4" 2 10 3/8" 3 13 1/2" 4 20 3/4" 5 25 1"	AA

(S) 6 – (S) 25 – PLASTIC



PLUG (COUPLER)



CAP (NIPPLE)

(S)	RED	BLUE	YELLOW	GREEN	BLACK	GREY
6	*	*	*	*	*	125.5371AA
10	*	*	*	*	*	125.5372AA
13	*	*	*	*	*	125.5373AA
20	*	*	*	*	*	125.5374AA
25	*	*	*	*	*	125.5375AA

* Not available.

(S)	RED	BLUE	YELLOW	GREEN	BLACK	GREY
6	*	*	*	*	*	125.5471AA
10	*	*	*	*	*	125.5472AA
13	*	*	*	*	*	125.5473AA
20	*	*	*	*	*	125.5474AA
25	*	*	*	*	*	125.5475AA

125-5

INTEVA reserves the right to make modifications to its products without prior notice. Any external or internal alterations to our products will automatically void the warranty.







125 SERIES TFH


TECHNICAL DATA

(S)	Min. Burst Pressure (Bar)			Max. Working Pressure
	Male	Female	Coupled	Bar
6	1650	1700	1800	450
10	1320	1400	1400	350
13	1100	1200	1200	300
19	1050	1100	1120	280
25	980	1050	1000	250
40	750	780	800	200

Test performed according to ISO 18869



FLOW SIMULATION



125-6

INTEVA reserves the right to make modifications to its products without prior notice. Any external or internal alterations to our products will automatically void the warranty.